

R A T E D L I F T I N G C A P A C I T I E S (L B S .)

CRANE MODEL: 4040C

ID NO.: MODEL 4040C

DATE: 9-27-2004

OVER THE REAR								
23 FEET BOOM			31 FEET BOOM			40 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
6	77	55540*						
8	72	45650*	8	78	42660*			
10	66	39380	10	74	36350	10	79	34560
12	60	31100	12	70	31220	12	75	30000
15	51	21220	15	63	21330	15	70	21380
18	39	15910	18	57	16020	18	65	16070
20	29	13550	20	52	13670	20	62	13710
			25	38	9840	25	53	9880
			30	14	7520	30	43	7590
						35	29	6050
						39	3	5120

* MAXIMUM LOAD WITH STANDARD REEVING IS 40000 LB.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	8340	16680	25020	33360	41700*	50040*	58380*	66720*

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED

QUIK MFG. COMPANY (Q M C)

RATED LIFTING CAPACITIES (L B S .)

CRANE MODEL: 4040C

ID NO.: MODEL 4040C

DATE: 9-27-2004

OVER THE SIDE								
23 FEET BOOM			31 FEET BOOM			40 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
6	77	55540*						
8	72	45650*	8	78	42660*			
10	66	39380	10	74	36350	10	79	34560
12	60	34790	12	70	31800	12	75	30000
15	51	29950	15	64	27080	15	71	25320
18	39	20400	18	57	20580	18	66	20680
20	29	16371	20	52	16550	20	62	16640
			25	38	10880	25	53	10950
			30	14	7880	30	43	7970
						35	29	6130
						39	3	5070

* MAXIMUM LOAD WITH STANDARD REEVING IS 40000 LB.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	8340	16680	25020	33360	41700*	50040*	58380*	66720*

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED

QUIK MFG. COMPANY (Q M C)

RATED LIFTING CAPACITIES (L B S .)

CRANE MODEL: 4040C

ID NO.: MODEL 4040C

DATE: 9-27-2004

OVER THE FRONT								
23 FEET BOOM			31 FEET BOOM			40 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
6	77	55880*						
8	72	45650*	8	78	42660*			
10	66	39380	10	74	36350	10	79	34560
12	60	34790	12	70	31800	12	75	30000
15	51	29950	15	64	27080	15	71	25320
18	39	19320F	18	57	19590F	18	66	19750F
20	29	14400F	20	52	14650F	20	62	14770F
			25	38	8660F	25	53	8760F
			30	14	5870F	30	42	5970F
						35	29	4370F
						39	3	3470F

* MAXIMUM LOAD WITH STANDARD REEVING IS 40000 LB.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	8340	16680	25020	33360	41700*	50040*	58380*	66720*

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED