

R A T E D L I F T I N G C A P A C I T I E S (L B S .)

CRANE MODEL: 5030R

ID NO.: MODEL 5030R

DATE: 8-20-2010

OVER THE REAR								
19 FEET BOOM			24 FEET BOOM			30 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
6	74	66720*						
8	68	61110*	8	74	56400*			
10	60	52490*	10	68	49180*	10	74	47010*
12	53	44340*	12	63	43210*	12	69	41260*
15	38	33010	15	54	33120	15	62	33160
18	0	25900	18	44	26260	18	55	26310
			20	36	23000	20	50	23070
			23.5	0	18700	25	34	17500
						29	0	14500

* MAXIMUM LOAD WITH STANDARD REEVING IS 40000 LB.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	8340	16680	25020	33360	41700*	50040*	58380*	66720*

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED

Q U I K M F G . C O M P A N Y (Q M C)

R A T E D L I F T I N G C A P A C I T I E S (L B S .)

CRANE MODEL: 5030R

ID NO.: MODEL 5030R

DATE: 8-20-2010

OVER THE SIDE								
19 FEET BOOM			24 FEET BOOM			30 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
6	74	66720*						
8	68	61110*	8	74	56400*			
10	60	52490*	10	68	49180*	10	74	47010*
12	53	46350*	12	63	43210*	12	69	41260*
15	38	39580	15	54	37040	15	63	35030
18	0	27500	18	44	32420	18	55	30670
			20	36	26930	20	50	27050
			23.5	0	19400	25	34	17550
						29	0	13400

* MAXIMUM LOAD WITH STANDARD REEVING IS 40000 LB.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	8340	16680	25020	33360	41700*	50040*	58380*	66720*

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED

Q U I K M F G . C O M P A N Y (Q M C)

R A T E D L I F T I N G C A P A C I T I E S (L B S .)

CRANE MODEL: 5030R

ID NO.: MODEL 5030R

DATE: 8-20-2010

OVER THE FRONT								
19 FEET BOOM			24 FEET BOOM			30 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
6	74	66720*						
8	68	61110*	8	74	56400*			
10	60	52490*	10	68	49180*	10	74	47010*
12	53	46350*	12	63	43210*	12	69	41260*
15	38	39580	15	54	37040	15	63	35030
18	10	27500	18	44	32420	18	55	30670
			20	36	29780	20	50	28380
			23.5	0	20800	25	35	23710
						29	0	16600

* MAXIMUM LOAD WITH STANDARD REEVING IS 40000 LB.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	8340	16680	25020	33360	41700*	50040*	58380*	66720*

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED