

R A T E D L I F T I N G C A P A C I T I E S (L B S .)

CRANE MODEL: 3570TD

ID NO.: MODEL 3570TD

DATE: 7-21-2004

OVER THE REAR								
30 FEET BOOM			50 FEET BOOM			70 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
6	81	52290*						
8	77	41790*						
10	73	35150*						
12	68	30560*	12	79	27260			
15	62	25960	15	75	22460			
18	55	22580	18	71	19190	18	79	17550
20	50	20810	20	69	17520	20	77	15900
25	34	16270	25	62	14450	25	72	12870
			30	55	12330	30	68	10810
			35	47	10530	35	63	9310
			40	38	8280	40	58	8160
			45	26	6620	45	53	6640
						50	47	5410
						55	40	4440
						60	33	3670
						65	23	3030
						69	3	2580

* MAXIMUM LOAD WITH STANDARD REEVING IS 29600 LB.
TRACTOR MUST BE ATTACHED.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	7400	14800	22200	29600	37000*	44400*	51800*	59200*

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED

QUIK MFG. COMPANY (Q M C)

RATED LIFTING CAPACITIES (L B S .)

CRANE MODEL: 3570TD

ID NO.: MODEL 3570TD

DATE: 7-21-2004

OVER THE SIDE								
30 FEET BOOM			50 FEET BOOM			70 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
6	81	52290*						
8	77	41790*						
10	73	35150*						
12	68	30560*	12	79	27260			
15	62	25960	15	75	22460			
18	55	22580	18	71	19190	18	79	17550
20	50	20810	20	69	17520	20	77	15900
25	34	15650	25	62	14450	25	72	12870
			30	55	11780	30	68	10810
			35	47	8890S	35	63	8900
			40	38	6930S	40	58	6940
			45	26	5500S	45	52	5520
						50	47	4450
						55	40	3610
						60	33	2940
						65	23	2370
						69	3	1970

* MAXIMUM LOAD WITH STANDARD REEVING IS 29600 LB.
TRACTOR MUST BE ATTACHED.

WIRE ROPE CAPACITY (L B S .)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	7400	14800	22200	29600	37000*	44400*	51800*	59200*

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED

QUIK MFG. COMPANY (Q M C)

RATED LIFTING CAPACITIES (L B S .)

CRANE MODEL: 3570TD

ID NO.: MODEL 3570TD

DATE: 7-21-2004

OVER THE FRONT								
30 FEET BOOM			50 FEET BOOM			70 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
6	81	52290*						
8	77	41790*						
10	73	35150*						
12	68	30560*	12	79	27260			
15	62	25960	15	75	22460			
18	55	22580	18	71	19190	18	79	17550
20	50	20810	20	69	17520	20	77	15900
25	34	16270	25	62	14450	25	72	12870
			30	55	12330	30	68	10810
			35	47	10530	35	63	9310
			40	38	8720	40	58	8160
			45	26	7300	45	53	7230
						50	47	6150
						55	41	5240
						60	33	4470
						65	23	3820
						69	3	3130

* MAXIMUM LOAD WITH STANDARD REEVING IS 29600 LB.
TRACTOR MUST BE ATTACHED.

WIRE ROPE CAPACITY (L B S .)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	7400	14800	22200	29600	37000*	44400*	51800*	59200*

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED