

R A T E D L I F T I N G C A P A C I T I E S (L B S .)

CRANE MODEL: 3630P

ID NO.: MODEL 3630P

DATE: 2-12-2003

OVER THE REAR								
19 FEET BOOM			24 FEET BOOM			30 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
6	74	52850*						
8	67	43550*	8	74	40900*			
10	60	37630*	10	68	34980*	10	74	33260*
12	52	31410	12	63	30870*	12	69	29370
15	38	24490	15	54	24560	15	63	24590
18	0	18030	18	44	18400	18	55	18480
			20	36	14710	20	50	14800
			23	0	10670	25	34	9680
						29	0	7400

* MAXIMUM LOAD WITH STANDARD REEVING IS 30000 LB.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	7600	15200	22800	30400*	38000*	45600*	53200*	0

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED

Q U I K M F G . C O M P A N Y (Q M C)

R A T E D L I F T I N G C A P A C I T I E S (L B S .)

CRANE MODEL: 3630P

ID NO.: MODEL 3630P

DATE: 2-12-2003

OVER THE SIDE								
19 FEET BOOM			24 FEET BOOM			30 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
6	74	52850*						
8	67	43550*	8	74	40900*			
10	60	37630*	10	68	34980*	10	74	33260*
12	52	33450*	12	63	30870*	12	69	29370
15	38	24580	15	54	24750	15	63	24840
18	0	15960	18	44	16291	18	55	16371
			20	35	13150	20	50	13230
			23	0	9630	25	34	8760
						29	0	6720

* MAXIMUM LOAD WITH STANDARD REEVING IS 30000 LB.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	7600	15200	22800	30400*	38000*	45600*	53200*	0

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED

Q U I K M F G . C O M P A N Y (Q M C)

R A T E D L I F T I N G C A P A C I T I E S (L B S .)

CRANE MODEL: 3630P

ID NO.: MODEL 3630P

DATE: 2-12-2003

OVER THE FRONT								
19 FEET BOOM			24 FEET BOOM			30 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
6	74	52850*						
8	67	43550*	8	74	40900*			
10	60	37630*	10	68	34980*	10	74	33260*
12	52	33450*	12	63	30870*	12	69	29370
15	38	29010	15	54	26720	15	63	25060
18	0	21660	18	44	23590	18	55	22070
			20	36	21850	20	50	20510
			23	0	16420	25	35	17410
						29	0	13130

* MAXIMUM LOAD WITH STANDARD REEVING IS 30000 LB.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	7600	15200	22800	30400*	38000*	45600*	53200*	0

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED