

R A T E D L I F T I N G C A P A C I T I E S ( L B S . )

CRANE MODEL: 3637T

ID NO.: MODEL 3637T

DATE: 7-27-2004

OVER THE REAR								
23 FEET BOOM			30 FEET BOOM			37 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
6	77	52170*						
8	72	42520*	8	77	40160*			
10	66	36400*	10	73	34030*	10	78	32520*
12	60	32140*	12	69	30000*	12	74	28480
15	51	27810	15	62	25540	15	69	24050
18	39	24470	18	55	22450	18	63	21000
20	29	22470	20	50	20840	20	60	19440
			25	34	16361	25	50	16450
						30	37	11990
						35	17	9280
						36	4	8830

\* MAXIMUM LOAD WITH STANDARD REEVING IS 30000 LB.  
TRACTOR MUST BE ATTACHED.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	7600	15200	22800	30400*	38000*	45600*	53200*	0

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED

RATED LIFTING CAPACITIES ( L B S . )
--------------------------------------

CRANE MODEL: 3637T

ID NO.: MODEL 3637T

DATE: 7-27-2004

OVER THE SIDE								
23 FEET BOOM			30 FEET BOOM			37 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
6	77	52170*						
8	72	42520*	8	77	40160*			
10	66	36400*	10	73	34030*	10	78	32520*
12	60	32140*	12	69	30000*	12	74	28480
15	51	27810	15	62	25540	15	69	24050
18	39	24470	18	55	22450	18	63	21000
20	29	22110	20	50	20840	20	60	19440
			25	34	14800	25	49	14900
						30	37	10930
						35	17	8480
						36	3	8070

\* MAXIMUM LOAD WITH STANDARD REEVING IS 30000 LB.  
TRACTOR MUST BE ATTACHED.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	7600	15200	22800	30400*	38000*	45600*	53200*	0

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED

RATED LIFTING CAPACITIES ( L B S . )

CRANE MODEL: 3637T

ID NO.: MODEL 3637T

DATE: 7-27-2004

OVER THE FRONT								
23 FEET BOOM			30 FEET BOOM			37 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
6	77	52170*						
8	72	42520*	8	77	40160*			
10	66	36400*	10	73	34030*	10	78	32520*
12	60	32140*	12	69	30000*	12	74	28480
15	51	27810	15	62	25540	15	69	24050
18	39	24470	18	55	22450	18	63	21000
20	29	22470	20	50	20840	20	60	19440
			25	34	17630	25	50	16520
						30	37	14370
						35	17	12140
						36	4	10640

\* MAXIMUM LOAD WITH STANDARD REEVING IS 30000 LB.  
TRACTOR MUST BE ATTACHED.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	7600	15200	22800	30400*	38000*	45600*	53200*	0

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED