

R A T E D L I F T I N G C A P A C I T I E S (L B S .)

CRANE MODEL: 3855C

ID NO.: MODEL 3855C

DATE: 11-30-2005

OVER THE REAR								
24 FEET BOOM			39 FEET BOOM			55 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
6	78	49260*						
8	72	42540*						
10	67	37370*	10	78	33260*			
12	61	27570	12	75	27180			
15	52	19290	15	70	18940	15	77	19450
18	42	14560	18	65	14250	18	74	14730
20	33	12380	20	61	12100	20	71	12570
			25	52	8510	25	65	8970
			30	41	6300	30	59	6750
			35	27	4790	35	52	5250
						40	45	4160
						45	36	3340
						50	25	2690
						54	3	2230

* MAXIMUM LOAD WITH STANDARD REEVING IS 30000 LB.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	7600	15200	22800	30400*	38000*	45600*	53200*	60800*

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED

Q U I K M F G . C O M P A N Y (Q M C)

R A T E D L I F T I N G C A P A C I T I E S (L B S .)

CRANE MODEL: 3855C

ID NO.: MODEL 3855C

DATE: 11-30-2005

OVER THE SIDE								
24 FEET BOOM			39 FEET BOOM			55 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
6	78	49260*						
8	72	42540*						
10	67	37380*	10	78	33260*			
12	62	33250*	12	75	28950			
15	53	28430	15	70	24140	15	78	22590
18	42	21040	18	65	20600	18	74	19320
20	33	16710	20	61	16330	20	72	17050
			25	52	10320	25	65	10940
			30	41	7160	30	59	7730
			35	27	5200	35	52	5760
						40	45	4420
						45	36	3440
						50	25	2700
						54	3	2190

* MAXIMUM LOAD WITH STANDARD REEVING IS 30000 LB.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	7600	15200	22800	30400*	38000*	45600*	53200*	60800*

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED

QUIK MFG. COMPANY (Q M C)

RATED LIFTING CAPACITIES (L B S .)

CRANE MODEL: 3855C

ID NO.: MODEL 3855C

DATE: 11-30-2005

OVER THE FRONT								
24 FEET BOOM			39 FEET BOOM			55 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
6	78	54960*						
8	73	44510*						
10	67	37880*	10	78	33260*			
12	62	33260*	12	75	28950			
15	53	28610	15	70	24140	15	78	22590
18	42	24610	18	65	20840	18	74	19320
20	33	21880	20	62	19150	20	72	17670
			25	52	12050	25	66	12940
			30	41	7520	30	59	8270
			35	27	5070	35	52	5760
						40	45	4200
						45	36	3120
						50	25	2330
						54	3	1810

* MAXIMUM LOAD WITH STANDARD REEVING IS 30000 LB.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	7600	15200	22800	30400*	38000*	45600*	53200*	60800*

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED