

R A T E D L I F T I N G C A P A C I T I E S (L B S .)

CRANE MODEL: 4030R

ID NO.: MODEL 4030R

DATE: 8-19-2008

OVER THE REAR								
19 FEET BOOM			24 FEET BOOM			30 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
6	74	53770*						
8	68	46620*	8	74	43780*			
10	60	40470*	10	68	37630	10	74	35730
12	53	35970	12	63	33200	12	69	31360
15	38	28150	15	54	28220	15	63	26790
18	0	21700	18	44	22140	18	55	22240
			20	36	17400	20	50	17490
			23.5	0	12400	25	34	11190
						29	0	8400

* MAXIMUM LOAD WITH STANDARD REEVING IS 40000 LB.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	8340	16680	25020	33360	41700*	50040*	58380*	0

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED

Q U I K M F G . C O M P A N Y (Q M C)

R A T E D L I F T I N G C A P A C I T I E S (L B S .)

CRANE MODEL: 4030R

ID NO.: MODEL 4030R

DATE: 8-19-2008

OVER THE SIDE								
19 FEET BOOM			24 FEET BOOM			30 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
6	74	54540*						
8	68	46620*	8	74	43780*			
10	60	40470*	10	68	37630	10	74	35730
12	53	35970	12	63	33200	12	69	31360
15	38	28220	15	54	28400	15	63	26790
18	0	17900	18	44	18200	18	55	18290
			20	36	14560	20	50	14650
			23.5	0	10500	25	34	9580
						29	0	7300

* MAXIMUM LOAD WITH STANDARD REEVING IS 40000 LB.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	8340	16680	25020	33360	41700*	50040*	58380*	0

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED

Q U I K M F G . C O M P A N Y (Q M C)

R A T E D L I F T I N G C A P A C I T I E S (L B S .)

CRANE MODEL: 4030R

ID NO.: MODEL 4030R

DATE: 8-19-2008

OVER THE FRONT								
19 FEET BOOM			24 FEET BOOM			30 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
6	74	56540*						
8	68	46620*	8	74	43780*			
10	60	40470*	10	68	37630	10	74	35730
12	53	35970	12	63	33200	12	69	31360
15	38	31010	15	54	28560	15	63	26790
18	0	23100	18	44	24790	18	56	23350
			20	36	22560	20	50	21290
			23.5	0	17600	25	35	17380
						29	0	14100

* MAXIMUM LOAD WITH STANDARD REEVING IS 40000 LB.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	8340	16680	25020	33360	41700*	50040*	58380*	0

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED