

R A T E D L I F T I N G C A P A C I T I E S (L B S .)

CRANE MODEL: 4170C

ID NO.: MODEL 4170C

DATE: 9-24-2004

OVER THE REAR								
30 FEET BOOM			50 FEET BOOM			70 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
8	76	47080*						
10	72	40860						
12	68	36480	12	78	30410			
15	61	29360	15	75	25790			
18	54	23770	18	71	22650	18	78	19900
20	49	21000	20	68	21060	20	77	18300
25	34	15980	25	62	16160	25	72	15370
			30	55	12740	30	68	12710
			35	47	10300	35	63	10280
			40	38	8480	40	58	8470
			45	26	7060	45	52	7070
						50	47	5950
						55	40	5030
						60	33	4260
						65	23	3610
						69	3	3120

* MAXIMUM LOAD WITH STANDARD REEVING IS 44000 LB.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	7400	14800	22200	29600	37000	44400*	51800*	59200*

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED

QUIK MFG. COMPANY (Q M C)

RATED LIFTING CAPACITIES (L B S .)

CRANE MODEL: 4170C

ID NO.: MODEL 4170C

DATE: 9-24-2004

OVER THE SIDE								
30 FEET BOOM			50 FEET BOOM			70 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
8	76	47080*						
10	72	40860						
12	68	36480	12	78	30410			
15	61	29360	15	75	25790			
18	54	23770	18	71	22650	18	78	19900
20	49	21000	20	68	21060	20	77	18300
25	34	15980	25	62	16160	25	72	15370
			30	55	12740	30	68	12710
			35	47	10300	35	63	10280
			40	38	8480	40	58	8470
			45	26	7060	45	52	7070
						50	47	5950
						55	40	5030
						60	33	4260
						65	23	3610S
						69	3	3090S

* MAXIMUM LOAD WITH STANDARD REEVING IS 44000 LB.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	7400	14800	22200	29600	37000	44400*	51800*	59200*

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED

QUIK MFG. COMPANY (Q M C)

RATED LIFTING CAPACITIES (L B S .)

CRANE MODEL: 4170C

ID NO.: MODEL 4170C

DATE: 9-24-2004

OVER THE FRONT								
30 FEET BOOM			50 FEET BOOM			70 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
8	76	47080*						
10	72	40860						
12	68	36480	12	78	30410			
15	61	29360	15	75	25790			
18	54	23770	18	71	22650	18	78	19900
20	49	21000	20	68	21060	20	77	18300
25	34	15980	25	62	16160	25	72	15370
			30	55	12740	30	68	12710
			35	47	10300	35	63	10280
			40	38	8480	40	58	8470
			45	26	7060	45	52	7070
						50	47	5950
						55	40	5030
						60	33	4260
						65	23	3610
						69	3	3120

* MAXIMUM LOAD WITH STANDARD REEVING IS 44000 LB.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	7400	14800	22200	29600	37000	44400*	51800*	59200*

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED