

R A T E D L I F T I N G C A P A C I T I E S (L B S .)

CRANE MODEL: 5370R

ID NO.: MODEL 5370R

DATE: 9-23-2011

OVER THE REAR								
30 FEET BOOM			50 FEET BOOM			70 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
6	81	52330*						
8	77	41830*						
10	73	35200*						
12	68	30610*	12	79	27200			
15	62	26000	15	75	22410			
18	55	22230	18	71	19130	18	79	17460
20	50	19590	20	69	17460	20	77	15810
25	34	14880	25	62	14390	25	72	12780
29	0	11600	30	55	11760	30	68	10720
			35	47	9570	35	63	9220
			40	38	7430	40	58	7380
			45	26	5890	45	52	5850
			49	0	4900	50	47	4710
						55	40	3820
						60	33	3100
						65	23	2510
						69	0	2000

* MAXIMUM LOAD WITH STANDARD REEVING IS 29600 LB.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	7400	14800	22200	29600	37000*	44400*	51800*	59200*

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED

QUIK MFG. COMPANY (Q M C)

RATED LIFTING CAPACITIES (L B S .)

CRANE MODEL: 5370R

ID NO.: MODEL 5370R

DATE: 9-23-2011

OVER THE SIDE								
30 FEET BOOM			50 FEET BOOM			70 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
6	81	52330*						
8	77	41830*						
10	73	35200*						
12	68	30610*	12	79	27200			
15	62	26000	15	75	22410			
18	55	22630	18	71	19130	18	79	17460
20	50	20860	20	69	17460	20	77	15810
25	34	16320	25	62	14390	25	72	12780
29	0	11700	30	55	12270	30	68	10720
			35	47	9460	35	63	9220
			40	38	7350	40	58	7290
			45	26	5820	45	52	5780
			49	0	4800	50	47	4650
						55	40	3770
						60	33	3050
						65	23	2470
						69	0	2000

* MAXIMUM LOAD WITH STANDARD REEVING IS 29600 LB.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	7400	14800	22200	29600	37000*	44400*	51800*	59200*

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED

QUIK MFG. COMPANY (Q M C)

RATED LIFTING CAPACITIES (L B S .)

CRANE MODEL: 5370R

ID NO.: MODEL 5370R

DATE: 9-23-2011

OVER THE FRONT								
30 FEET BOOM			50 FEET BOOM			70 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
6	81	52330*						
8	77	41830*						
10	73	35200*						
12	68	30610*	12	79	27200			
15	62	26000	15	75	22410			
18	55	22630	18	71	19130	18	79	17460
20	50	20860	20	69	17460	20	77	15810
25	34	16320	25	62	14390	25	72	12780
29	0	11700	30	55	12270	30	68	10720
			35	47	10470	35	63	9220
			40	38	8650	40	58	8061
			45	26	7230	45	53	7140
			49	0	5500	50	47	6050
						55	41	5130
						60	33	4370
						65	23	3720
						69	0	2700

* MAXIMUM LOAD WITH STANDARD REEVING IS 29600 LB.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	7400	14800	22200	29600	37000*	44400*	51800*	59200*

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED