

R A T E D L I F T I N G C A P A C I T I E S ( L B S . )

CRANE MODEL: 5967S

ID NO.: MODEL 5967S

DATE: 10- 4-2004

OVER THE REAR								
27 FEET BOOM			47 FEET BOOM			67 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
6	79	58790*						
8	75	48780*						
10	70	42500*	10	80	35590*			
12	65	38040*	12	77	31120*			
15	58	29520	15	73	26710			
18	49	23960	18	70	23550	18	78	18070
20	43	21210	20	67	21400	20	76	16350
25	21	16140	25	60	16390	25	71	13000
			30	52	12970	30	66	10720
			35	43	10550	35	61	9030
			40	33	8730	40	56	7730
			45	16	7300	45	50	6610
						50	44	5770
						55	37	5060
						60	28	4480
						65	14	3880
						66	3	3720

\* MAXIMUM LOAD WITH STANDARD REEVING IS 29600 LB.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	7400	14800	22200	29600	37000*	44400*	51800*	59200*

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED

QUIK MFG. COMPANY ( Q M C )

RATED LIFTING CAPACITIES ( L B S . )

CRANE MODEL: 5967S

ID NO.: MODEL 5967S

DATE: 10- 4-2004

OVER THE SIDE								
27 FEET BOOM			47 FEET BOOM			67 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
6	79	58790*						
8	75	48780*						
10	70	42500*	10	80	35590*			
12	65	38040*	12	77	31120*			
15	58	29520	15	73	26710			
18	49	23960	18	70	23550	18	78	18070
20	43	21210	20	67	21400	20	76	16350
25	21	16140	25	60	16390	25	71	13000
			30	52	11110	30	66	10730
			35	43	7770	35	61	7880
			40	32	5680	40	55	5790
			45	15	4240	45	50	4370
						50	43	3330
						55	36	2550
						60	27	1920
						65	13	1410
						66	2	1280

\* MAXIMUM LOAD WITH STANDARD REEVING IS 29600 LB.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	7400	14800	22200	29600	37000*	44400*	51800*	59200*

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED

QUIK MFG. COMPANY ( Q M C )

RATED LIFTING CAPACITIES ( L B S . )

CRANE MODEL: 5967S

ID NO.: MODEL 5967S

DATE: 10- 4-2004

OVER THE FRONT								
27 FEET BOOM			47 FEET BOOM			67 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
6	79	58790*						
8	75	48780*						
10	70	42500*	10	80	35590*			
12	65	38040*	12	77	31120*			
15	58	29520	15	73	26710			
18	49	18290	18	69	18810	18	77	18050
20	43	13940	20	66	14400	20	75	14550
25	21	8090	25	59	8540	25	70	8640
			30	51	5620	30	65	5700
			35	43	3860	35	60	3930
			40	32	2680	40	55	2750
			45	15	1820	45	49	1910
						50	43	1280
						55	36	780
						60	27	0
						65	13	0
						66	2	0

\* MAXIMUM LOAD WITH STANDARD REEVING IS 29600 LB.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	7400	14800	22200	29600	37000*	44400*	51800*	59200*

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED