

R A T E D L I F T I N G C A P A C I T I E S (L B S .)

CRANE MODEL: 6070TD

ID NO.: MODEL 6070TD

DATE: 4-20-2004

OVER THE REAR								
31 FEET BOOM			51 FEET BOOM			71 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
8	77	65180*						
10	73	57680*						
12	69	51650*	12	78	44170*			
15	62	43980	15	75	37580			
18	55	35440	18	71	33100	18	79	29410
20	50	28250	20	69	28530	20	77	26810
25	35	17890	25	62	18160	25	72	18210
			30	55	12840	30	67	12890
			35	47	9610	35	62	9650
			40	39	7430	40	57	7470
			45	27	5850	45	52	5910
						50	46	4730
						55	40	3800
						60	33	3060
						65	23	2440
						69	2	1930

* MAXIMUM LOAD WITH STANDARD REEVING IS 44000 LB.
TRACTOR MUST BE ATTACHED.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	7600	15200	22800	30400	38000	45600*	53200*	60800*

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED

Q U I K M F G . C O M P A N Y (Q M C)

R A T E D L I F T I N G C A P A C I T I E S (L B S .)

CRANE MODEL: 6070TD

ID NO.: MODEL 6070TD

DATE: 4-20-2004

OVER THE SIDE								
31 FEET BOOM			51 FEET BOOM			71 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
8	77	65180*						
10	73	57680*						
12	69	51650*	12	78	44170*			
15	62	43980	15	75	37580			
18	55	31500	18	71	31780	18	79	29410
20	50	25090	20	68	25360	20	77	25430
25	35	16060	25	62	16310	25	72	16361
			30	55	11570	30	67	11610
			35	47	8650	35	62	8680
			40	38	6660	40	57	6700
			45	27	5210	45	52	5260
						50	46	4180
						55	40	3320
						60	33	2630
						65	23	2060
						69	2	1580

* MAXIMUM LOAD WITH STANDARD REEVING IS 44000 LB.
TRACTOR MUST BE ATTACHED.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	7600	15200	22800	30400	38000	45600*	53200*	60800*

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED

Q U I K M F G . C O M P A N Y (Q M C)

R A T E D L I F T I N G C A P A C I T I E S (L B S .)

CRANE MODEL: 6070TD

ID NO.: MODEL 6070TD

DATE: 4-20-2004

OVER THE FRONT								
31 FEET BOOM			51 FEET BOOM			71 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
8	77	67470*						
10	73	58410*						
12	69	52200*	12	78	44170*			
15	62	43980	15	75	37580			
18	55	35860	18	71	33100	18	79	29410
20	50	31750	20	69	30650	20	77	26810
25	36	24240	25	62	23900	25	72	21610
			30	55	19330	30	68	18040
			35	48	16031	35	63	15340
			40	39	13540	40	58	13200
			45	28	11580	45	53	11580
						50	47	10020
						55	41	8620
						60	34	7380
						65	24	6360
						69	3	5490

* MAXIMUM LOAD WITH STANDARD REEVING IS 44000 LB.
TRACTOR MUST BE ATTACHED.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	7600	15200	22800	30400	38000	45600*	53200*	60800*

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED