

RATED LIFTING CAPACITIES (LBS.)
PRELIMINARY

CRANE MODEL: 7060RSX

ID NO.: MODEL 7060RSX

DATE: 2- 8-2017

360 DEGREES CHART											
38 FEET BOOM			45 FEET BOOM			53 FEET BOOM			60 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
6	77	60000*	6	79	60000*						
8	74	60000*	8	77	60000*	8	79	60000*			
10	71	58700	10	74	58700	10	77	58700	10	80	58700
12	67	52700	12	72	52700	12	75	52800	12	78	52700
15	62	45600	15	67	45600	15	71	45700	15	75	45600
18	57	39500	18	63	39600	18	68	39700	18	71	39800
20	53	34200	20	60	34400	20	65	34400	20	69	34500
25	42	25100	25	52	25400	25	59	25500	25	64	25600
30	29	17900	30	43	18100	30	52	18300	30	58	18300
			35	33	13700	35	44	13900	35	52	14000
			40	17	10800	40	36	10900	40	45	11000
						45	24	8800	45	38	8900
									50	28	7300
									55	14	6100
									56	0	5600

* CAPACITY IS LIMITED BY THE REEVING

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	11250	22500	33750	45000	56250	67500*	0	0

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED